

§ 1918.95

(d) *Other fumigated cargoes.* Before commencing to load or discharge fumigated cargo other than the cargo specifically addressed in paragraphs (b) and (c) of this section, the employer shall determine that the concentration of fumigants is within the level specified as hazardous by the fumigant manufacturer, or does not exceed the permissible exposure limits of part 1910, subpart Z of this chapter, whichever is lower.

(e) *Grain dust.* When employees are exposed to concentrations of grain dust greater than the allowable limit found in subpart Z of part 1910 of this chapter, they shall be protected by suitable respiratory protective equipment as required by § 1918.102.

(f) *Catch of menhaden and similar species of fish.* (1) The provisions of this paragraph shall not apply to vessels having and utilizing refrigerated holds for the carriage of all cargo.

(2) After a vessel has arrived at berth for discharge of menhaden, but before personnel enter the hold, and as frequently thereafter as tests show to be necessary, tests shall be made of the atmosphere in the vessel's hold to ensure a safe work space. The tests shall be done for the presence of hydrogen sulfide and for oxygen deficiency.

(3) Tests required by paragraph (f)(2) of this section shall be made by designated supervisory personnel, trained and competent in the nature of hazards and the use of test equipment and procedures.

(4) Before employees enter a hold it shall be tested for hydrogen sulfide and oxygen deficiency. Employees shall not enter the hold when the hydrogen sulfide level exceeds 20 ppm ceiling or when the oxygen content is less than 19.5 percent, except in emergencies.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40946, June 30, 2000]

§ 1918.95 Sanitation.

(a) *Washing and toilet facilities.* (1) Accessible washing and toilet facilities sufficient for the sanitary requirements of employees shall be readily accessible at the worksite. The facilities shall have:

(i) Running water, including hot and cold or tepid water, at a minimum of one accessible location (when

29 CFR Ch. XVII (7–1–11 Edition)

longshoring operations are conducted at locations without permanent facilities, potable water may be provided instead of running water);

(ii) Soap;

(iii) Individual hand towels, clean individual sections of continuous toweling, or warm air blowers; and

(iv) Fixed or portable toilets in separate compartments with latch-equipped doors. Separate toilet facilities shall be provided for male and female employees unless toilet rooms will be occupied by only one person at a time.

(2) Washing and toilet facilities shall be regularly cleaned and maintained in good order.

(b) *Drinking water.* (1) Potable drinking water shall be accessible to employees at all times.

(2) Potable drinking water containers shall be clean, containing only water and ice, and shall be fitted with covers.

(3) Common drinking cups are prohibited.

(c) *Prohibited eating areas.* Consumption of food or beverages in areas where hazardous materials are stowed or being handled is prohibited.

(d) *Garbage and overboard discharges.* Work shall not be conducted close to uncovered garbage or in the way of overboard discharges from the vessel's sanitary lines unless employees are protected from the garbage or discharge by a baffle or splash boards.

EFFECTIVE DATE NOTE: At 76 FR 33610, June 8, 2011, § 1918.95 was amended by revising paragraph (a)(1)(iii), effective July 8, 2011. For the convenience of the user, the added and revised text is set forth as follows:

§ 1918.95 Sanitation.

(a) * * *

(1) * * *

(iii) Individual hand towels, clean individual sections of continuous toweling, or air blowers; and

* * * * *

§ 1918.96 Maintenance and repair work in the vicinity of longshoring operations.

(a) *Noise interference* (See also § 1918.1(b)(6).) Longshoring operations shall not be carried on when noise interferes with communications of warnings or instructions.

(b) *Falling objects.* Longshoring operations shall not be carried on in the hold or on deck beneath work being conducted overhead whenever such work exposes the employee to a hazard of falling objects.

(c) *Hot work.* Longshoring operations shall not be carried on where the employee is exposed to damaging light rays, hot metal, or sparks from welding or cutting.

(d) *Abrasive blasting and spray painting.* Longshoring operations shall not be carried on in the immediate vicinity of abrasive blasting or spray painting operations.

(e) *Machine guarding.* (See also § 1918.2, definition of "Danger zone".)

(1) Danger zones on machines and equipment used by employees shall be guarded.

(2) The power supply to machines shall be turned off, locked out, and tagged out during repair, adjustment, or servicing.

§ 1918.97 First aid and lifesaving facilities. (See appendix V of this part).

(a) *Injury reporting.* The employer shall require each employee to report every work-related injury, regardless of severity, to the employer.

(b) *First aid.* A first aid kit shall be available at or near each vessel being worked. At least one person holding a valid first aid certificate, such as is issued by the Red Cross or other equivalent organization, shall be available to render first aid when work is in progress.

(c) *First aid kits.* First aid kits shall be weatherproof and shall contain individual sealed packages for each item that must be kept sterile. The contents of each kit shall be determined by a person certified in first aid and cognizant of the hazards found in marine cargo handling operations. The contents shall be checked at intervals that allow prompt replacement of expended items.

(d) *Stretchers.* (1) For each vessel being worked, at least one Stokes basket stretcher, or its equivalent, shall be available to be permanently equipped with bridles for attachment to the hoisting gear.

(2) Stretchers shall be kept close to vessels and shall be positioned to avoid damage to the stretcher.

(3) A blanket or other suitable covering shall be available.

(4) Stretchers shall have at least four sets of effective patient restraints in operable condition.

(5) Lifting bridles shall be of adequate strength, capable of lifting 1,000 pounds (454 kg) with a safety factor of five (lifting capability of 5,000 pounds), and shall be maintained in operable condition. Lifting bridles shall be provided for making vertical patient lifts at container berths. Stretchers for vertical lifts shall have foot plates.

(6) Stretchers shall be maintained in operable condition. Struts and braces shall be inspected for damage. Wire mesh shall be secured and have no burrs. Damaged stretchers shall not be used until repaired.

(7) Stretchers in permanent locations shall be mounted to prevent damage and be protected from the elements if located out-of-doors. If concealed from view, enclosures shall be marked to indicate the location of the lifesaving equipment.

(e) *Life-rings.* (1) The employer shall ensure that there is in the vicinity of each vessel being worked at least one U.S. Coast Guard approved 30-inch (76.2 cm) life-ring with no less than 90 feet (27.43 m) of line attached, and at least one portable or permanent ladder that will reach from the top of the apron to the surface of the water.

(2) In addition, when working a barge, scow, raft, lighter, log boom, or carfloat alongside a ship, a U.S. Coast Guard approved 30-inch (76.2 cm) life-ring, with no less than 90 feet (27.43 m) of line shall be provided either on the floating unit itself or aboard the ship in the immediate vicinity of each floating unit being worked.

(f) *Communication.* Telephone or equivalent means of communication shall be readily available at the work-site.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40946, June 30, 2000]

§ 1918.98 Qualifications of machinery operators and supervisory training.

(a) *Qualification of machinery operators.* (1) Only an employee determined